

OpenCPI

Time Demux Component Data Sheet

OpenCPI Release: v2.3.4

Summary - Time Demux

Name	time_demux
Worker Type	Application
OpenCPI Release	v2.3.4
Last Update	04/2019
Component Library	ocpi.training.components
Workers	time_demux.rcc
Tested Platforms	c7-x86_64, linux-zynq-arm

Functionality

The Time Demux component acts as a demultiplexer/router by parsing an `iqstream_with_sync` protocol and routing timestamps and data to separate output ports.

The incoming `iqstream_with_sync` supports three opcodes: `iq`, `Sync`, and `Time`. The output ports use the `iqstream` and `iqstream_with_sync` protocols, the former using a single opcode. Data within the `iqstream_with_sync`'s `Time` opcode (a single 64-bit value) is passed directly through, while data within the `iq` opcode is converted to `iqstream`'s `iq` opcode's data (which, conveniently, is the same structure). The `iqstream_with_sync`'s `Sync` opcode is currently ignored.

Block Diagrams

Top level



Figure 1: Top-level Block Diagram

Source Dependencies

time_demux.rcc

- training/components/time_demux.rcc/time_demux.cc

Test and Verification

This component uses the standard OpenCPI test process. It is one of the few that use multiple ports.

The only currently known issue is that the specfile must define the “Data.Out” port *first* to have the test application use it to signal “done.”

Advanced / Detailed Theory of Operation

This section is not essential to understand to perform the training lab.

Testing of the Time Demux component consists of a C++ program (*test_data_generator.cxx*) used to generate input data and expected “golden” outputs (Figure 2).

Fake timestamps and sample data are interleaved into an input file using the “message mode” format required to have *ocpi.file_read* playback opcodes with data. The C++ generator takes input arguments of: input file name, starting timestamp, number of samples to push each “second,” filename for the interleaved file, filename for the golden timestamps, and filename for the golden output file. These parameters are all handled by the OpenCPI test XML, with the test application shown in Figure 3.

Output data is compared to the golden file(s) by the Makefile (Figure 4).




Figure 2: C++ Generator Usage




Figure 3: Test Application Layout (*app_time_demux*)




Figure 4: Testing

The default XML provides reasonable values for each of the data generator's required parameters:

Test Property	Default	Notes
IFILE	(Running kernel image) <i>e.g.</i> /boot/vmlinuz-3.10.0-327.4.4.el7.x86_64	The input file is truncated to a 32-bit boundary to simulate two 16-bit data samples. This may cause verification issues if using random files.
START	0	Decimal only
SAMPLES	256	Should not exceed 2048

For test purposes, the “timestamp” is a one-up counter starting at START placed in the upper 32-bits and then incremented and placed into the lower 32-bits:

```
$ od -t x8 odata/output_time_golden.bin | head
0000000 000000000000000001 0000000100000002
0000020 00000002000000003 0000000300000004
0000040 00000004000000005 0000000500000006
0000060 00000006000000007 0000000700000008
0000100 00000008000000009 000000090000000a
0000120 0000000a0000000b 0000000b0000000c
0000140 0000000c0000000d 0000000d0000000e
0000160 0000000e0000000f 0000000f00000010
0000200 0000001000000011 0000001100000012
0000220 0000001200000013 0000001300000014
```